

Critical Material Technologies for Battery Energy Storage Systems

A Guide to Material Selection, Integration, and Manufacturing Readiness

As battery energy storage systems (BESS) continue to increase in capacity and energy density, engineering teams face growing pressure to improve performance while maintaining safety, reliability, manufacturability, and cost targets. Many system-level design decisions are shaped by material selection. Decisions involving thermal management, electrical isolation, venting, environmental protection, and mechanical design can affect thermal runaway mitigation, enclosure design, serviceability, and production scalability.

For sourcing teams, considerations extend beyond technical specifications. Sourcing strategies, material availability, manufacturing capabilities, qualification requirements, and production readiness can all drive program timelines and deployment success. While no single material determines system performance,

engineered materials play critical roles throughout cells, modules, packs, and enclosures. Understanding how these technologies interact helps teams make more informed design and sourcing decisions.

This document outlines key engineered material technologies used in BESS platforms and the design, manufacturing, and integration considerations that influence battery system development.

BOYD
TRUSTED INNOVATION




Image: Engineered Materials Across the Battery Energy Storage System Assembly

Emerging Material Challenges in Modern BESS Designs

Before evaluating individual materials, it is important to consider the broader industry trends shaping battery system architecture.

- **Faster commercialization timelines:** Many manufacturers face pressure to accelerate development cycles. Materials that perform well technically must also support efficient qualification and production ramp schedules.
- **Manufacturability at scale:** The highest performing material is not always the easiest to process, source globally, or manufacture consistently across production volumes.
- **Supply chain resilience:** Engineering and sourcing teams increasingly evaluate supplier capabilities, regional manufacturing flexibility, and supply continuity alongside material performance specifications.
- **System-level optimization:** Material technologies do not operate independently. Decisions affecting thermal management, electrical isolation, venting, and sealing often influence one another throughout the system.

1 | Thermal Runaway Protection

Managing heat transfer, venting, and system-level thermal protection

Thermal runaway mitigation involves more than preventing cell-to-cell propagation. Manufacturers must also consider how heat, gases, particulates, and pressure are managed throughout the battery system when a cell failure occurs. These events can affect enclosure design, venting strategies, system architecture, and material selection.

Thermal barriers, blast barriers, and insulation materials each serve different functions within a protection strategy. Thermal barriers are used to slow heat transfer between cells, modules, and other critical areas. Blast barriers help manage venting events by containing particulates and protecting nearby components. Insulation blankets provide localized thermal protection around enclosure covers, vent-facing regions, and areas exposed to elevated temperatures.

No single material addresses thermal runaway protection on its own. Effective strategies often require multiple solutions working together to manage heat

transfer, venting, and adjacent component protection. The goal is to balance protection, manufacturability, weight, and cost while supporting system-level performance requirements.

Common Design Challenge: Balancing thermal runaway protection requirements with space constraints, system weight, manufacturability, and cost targets.

Key Considerations:

- Thermal runaway mitigation objectives
- Cell and module architecture
- Venting and containment requirements
- Available design space and weight targets
- Material durability and service-life performance
- Installation and serviceability requirements
- Qualification and certification requirements

2 | Thermal Interface Materials

Improving heat transfer efficiency

Thermal interface materials (TIMs) help transfer heat from cells and modules to cooling surfaces, supporting temperature control across the battery system. Selecting the right TIM involves more than thermal conductivity alone. Material selection is often guided by interface geometry, cooling requirements, assembly tolerances, and manufacturing processes.

Engineers also evaluate compressibility, contact reliability, and long-term durability to help maintain consistent thermal performance throughout the life of the system. Maintaining reliable contact during operation is often just as important as achieving a target conductivity value.

Common Design Challenge: A TIM with higher conductivity doesn't automatically yield better performance if it cannot maintain consistent contact across production tolerances.

Key Considerations:

- Thermal conductivity: Heat transfer requirements at the interface
- Gap-filling capability: Gap dimensions, surface


irregularities, and assembly tolerances

- Mechanical properties: Conformability and compressibility
- Performance retention: Resistance to thermal aging and degradation
- Manufacturing compatibility: Material application method and process repeatability

3 | Dielectric Isolation & Insulation

Maintaining electrical protection

Dielectric films, barriers, and insulating materials maintain electrical isolation throughout the battery system, including around cells, busbars, terminals, and power distribution assemblies. Their performance depends not only on dielectric strength, but also on how well they withstand mechanical stress, thermal exposure, and manufacturing processes throughout the product lifecycle.



Selecting the right insulation solutions requires balancing electrical protection, durability, thickness, and assembly requirements. Designers must also consider creepage and clearance requirements, operating voltage, environmental conditions, and applicable safety standards.

Common Design Challenge: Providing reliable electrical protection while fitting within space constraints and maintaining durability throughout manufacturing and service-life operation.

Key Considerations:

- Voltage and dielectric requirements: Operating voltage and required insulation performance

- Creepage and clearance: Required separation distances based on system design and standards
- Thermal durability: Performance under expected operating conditions and thermal cycling
- Mechanical durability: Resistance to abrasion, vibration, compression, and handling damage
- Assembly integration: Fit, coverage, and compatibility with manufacturing processes
- Qualification and scalability: Validation requirements, production consistency, and ability to scale with demand

4 | Cell Compression Management

Maintaining cell expansion and stack pressure

Battery cells can change dimensions over time due to charge-discharge cycling, aging, and operating conditions. Managing these dimensional changes while preserving the intended stack pressure is an important consideration in many battery designs.

Compression materials manage cell expansion, maintain stack pressure, and distribute mechanical loads within the module. Compression requirements are influenced by cell chemistry, expansion characteristics, available space, and target pressure requirements. Initial compression alone is insufficient. The selected solution must maintain the required force throughout the expected battery service life.



Common Design Challenge: Maintaining consistent compression throughout battery life while balancing space constraints, durability requirements, and manufacturing considerations.

Key Considerations:

- Cell expansion characteristics: Expected dimensional changes over the life of the battery
- Compression requirements: Target pressure range and force-deflection behavior
- Compression durability: Resistance to compression set, stress relaxation, and aging
- Module integration: Available space, pad placement, and fit with the cell stack
- Thermal and operating conditions: Performance across expected temperature range & duty cycles
- Manufacturing tolerances: Dimensional control and assembly repeatability

5 | Enclosure Sealing

Protecting system integrity

Battery storage energy systems are often deployed in demanding outdoor environments and must withstand prolonged exposure to moisture, dust, temperature fluctuations, and vibration throughout their service life. Enclosure sealing protects electrical and mechanical components while supporting long-term system reliability.

Effective sealing depends on more than achieving a target IP or NEMA rating. Sealing integrity is affected by enclosure design, joint geometry, environmental conditions, manufacturing tolerances, and service access requirements.

Common Design Challenge: Protecting against environmental exposure while accommodating manufacturing tolerances and service requirements.

Key Considerations:

- Ingress protection: Required IP/ NEMA rating based on enclosure design and operating environment
- Environmental exposure: Resistance to UV exposure, moisture, chemicals, and extreme temperatures
- Tolerance accommodation: Ability to maintain sealing performance across dimensional variation and assembly tolerances
- Compression set: Ability to maintain sealing contact over time
- Durability: Resistance to vibration and thermal

cycling in systems requiring repeated access

- Assembly requirements: Installation time and method, and production repeatability
- Serviceability: Requirements for inspection, maintenance, and enclosure re-entry

System Level Integration

BESS material technologies serve distinct functions, but their selection and placement are interconnected. Thermal runaway protection solutions can affect available space and thermal management strategies. Electrical insulation influences component spacing and assembly methods. Venting requirements shape enclosure design, while sealing solutions may affect service access and maintenance considerations.

Material decisions should be evaluated in the context of the complete battery system rather than as individual components. For engineering and sourcing teams, this means considering performance requirements, integration constraints, qualification needs, and supplier capabilities together to support overall system objectives.

Manufacturing Readiness: From Design to Production

Material performance is only one factor in the material selection process. Availability, manufacturability, qualification requirements, and supply chain considerations ultimately impact material selection. A material that performs well in a prototype may create sourcing constraints, assembly challenges, or production delays as volumes increase. Evaluating

manufacturing requirements early helps teams identify these risks before they affect launch schedules, cost targets, or production scale-up.

Manufacturing Readiness Factors:

- Material and component qualification
- Supply continuity and sourcing flexibility
- Production capacity and scalability
- Regional manufacturing capabilities
- Quality systems and process control
- Prototyping, testing, and validation capabilities
- DFM and assembly efficiency

Boyd: Engineering Solutions for Scalable Manufacturing

Material decisions affect more than performance. They influence manufacturability, supplier selection, qualification timelines, and production readiness.

Boyd combines material expertise, engineering support, rapid prototyping, and in-house testing to help customers evaluate tradeoffs, validate designs, and address challenges early in development. From material selection through component design and production ramp, Boyd helps engineering and sourcing teams reduce risk and make informed decisions before they become manufacturing constraints.

With global manufacturing capabilities and quality systems designed for scale, Boyd supports programs from prototype builds through volume production across multiple regions.

Boyd is the trusted global innovator of sustainable solutions that make our customers' products better, safer, faster, and more reliable. Our innovative engineered materials advance our customers' technology to maximize performance in the world's most advanced data centers; advance the accuracy of cutting-edge personal healthcare and diagnostic systems; enable performance-critical aircraft and security technologies; enhance reliability and extend range for intelligent mobility applications; and accelerate innovation in next-generation electronics and human machine interface. To receive more information, please visit www.boydcorp.com